
Table Top Vacuum Chamber

Reliable and precise packaging results.



The Minipack MVS X Series is ideal for kitchens. retail counters. manufacturing operations. and laboratories. It is engineered for precise, hygienic and user-friendly vacuum packaging. A wide range of chamber sizes, seal bar types and lengths, vacuum pump capacities, and optional equipment make it easy to find the most efficient system for your needs. Our machines are designed with unique hygienic features, such as pop-out seal bars, excess bag cut-off, seamless chamber, and stainless steel housing.





Chamber & Seal Bars

seamless and easy to clean surfaces

Benefit from optimized throughput by the perfect combination of length, position, and type of seal bars. Pop-out seal bars, seamless chamber, and durable stainless steel construction allow for easy sanitation.

Performance

powerful and reliable

All models are equipped with a powerful Busch or DVP vacuum pump, which are able to process more than 2-3 cycles per minute. Choose a pump capacity from 4.8 m³/h up to 24 m³/h.



Display, Controls & Programmability

Enjoy our simple and intuitive machines. All machines are equipped with a water resistant digital display featuring user-settable preferences and up to 9 customizable programs. The electronic millibar sensor precisely measures the vacuum level and triggers the chosen sealing and de-evacuation modes.



SMART TECHNOLOGY FEATURES

- · Pop-out seal bars with options of convex seal, or top & bottom seal
- · Programmable sealing time: ensure optimized seal for any thickness of
- · External channel bag evacuation: vacuum and seal outside of the chamber
- · Excess bag cut-off: for food safety and better bag handling
- · Extra vacuum: run evacuation up to 30 seconds longer
- · 9 user-settable programs

- Tray for liquids vacuum liquid
- . Unique waffle-pattern sealing: special pattern offers the highest quality in seal strength
- · Hygienic seamless chamber
- · Service reminder: user-friendly preprogrammed reminder on standard maintenance
- · Evacuation filter kit: prevents oil and pump from contamination when vacuuming dusty products
- · Inert gas flush kit: option for modified atmosphere packaging







Food Processing



Six good reasons to choose minipack:

- Focused on value and user-centered innovation Over 40 years track record as innovator
- Reliability and cost advantage over the long run
- Committed to customer service and support
- Certified quality manufacturing ISO 9001:2000
- Worldwide distribution network and technical assistance

Table Top Vacuum Chamber



MVS 20



MVS 26X



MVS 26XII



MVS 31X



MVS 35X



MVS 45X





						- 1			
	Chamber Width x Length	8.75" x 12.00"	11.00" x 16.00"	11.00" x 16.00"	13.00" x 11.75"	13.00" x 11.75"	18.50" x 18.00"	18.50" x 18.00"	14.75" x 13.00"
Chamber & Seal Bars	Height (Chamber + Dome/Lid = Total)	3.00" + 1.25" = 4.25"	4.25" + 1.00" = 5.50"	4.25" + 1.00" = 5.50"	4.50" + 2.00" = 6.50"	4.50" + 3.00" = 7.50"	4.50" + 4.00" = 8.75"	4.50" + 4.00" = 8.75"	3.75"
	Number of Seal Bars (removable)	1	1	2	1	1	1	2	1
	Position of Seal Bars	Front	Front	Front & Back	Front	Front	Front	Left & Right	Front
	Seal Bar Length	8.50"	10.50"	2 x 10.50"	12.25"	12.25"	17,75"	2 x 17.75"	16.75"
	Distance between Seal Bars		2	12.00"	*	-	2	14.00"	72
	4 mm Seal + 1 mm Cut-Off Seal	/	/	/	/	/	1	1	/
	Unique Waffle-Pattern Sealing		7	/	7		1	1	-
	Hygienic Seamless Chamber	/	1	1	,	,	1	,	-
	Pop-Out Seal Bars	/	1	1	1	1	1	,	/
	Independent Power to each Seal Bar	J	1	1	,	,	./	Ż	
	Pump Type	Busch KB Oil Rotary	Busch KB Oil Rotary	Busch KB Oil Rotary	DVP LB6 Oil Rotary	Busch R5 Oil Rotary	Busch R5 Oil Rotary	Busch R5 Oil Rotary	Busch R5 Oil Rotary
	Cycles per Minute*	up to 3	up to 3	up to 3	up to 3	up to 3	up to 3	up to 3	up to 3
Performance	Free Air Displacement @ 50Hz	4 m³/h	6 m³/h	6 m³/h	6 m³/h	10 m³/h	20 m³/h	20 m³/h	20 m³/h
	Free Air Displacement @ 60Hz	5 m³/h	7 m³/h	7 m³/h	7 m³/h	12 m³/h	24 m³/h	24 m³/h	24 m³/h
	Pump Power Rating	0.25 hp	0.50 hp	0.50 hp	0.50 hp	0.75 hp	1.25 hp	1.25 hp	1.25 hp
	Power Supply	110V / 5.5A	120V / 12A	120V / 12A	120V / 7.5A	120V / 10A	120V / 17A	120V / 17A	1.25 lip
	Water Resistant Digital Display	- CHICAGONO CONTROLO	A CONTRACTOR	120V / 12A	A STATE OF THE STA	120V7 10A	12007174	120V117A	/ 110V / OA
Display & Controls	water Resistant Digital Display LED Display	<i>y</i>	· /	· · · · · · · · · · · · · · · · · · ·	· /	· · · · · · · · · · · · · · · · · · ·	1	· · · · · · · · · · · · · · · · · · ·	· · · · · · · · · · · · · · · · · · ·
		A.VA	V	V	V	Y	· · · · · · · · · · · · · · · · · · ·	· ·	· · · · · · · · · · · · · · · · · · ·
	Electronic Millibar Sensor	-	· ·	· ·	✓ •	✓	✓ ·	~	✓
	Customizable Programs	1	9	9	9	9	9	9	9
	Programmable Sealing Time	1	✓	1	✓	✓	✓	✓	1
	Programmable Vacuum Time	✓	✓	/	✓	✓	1	√	1
Operational	External Channel Bag Evacuation	✓	✓	✓	✓	✓		٠	(5)
Features	Extra Vacuum (30 sec)	*	✓	1	✓.	✓	1	✓	✓
	Excess Bag Cut-Off	1	✓	✓	✓	✓	✓	✓	✓
	High Volume Density Plates	✓	✓.	✓	✓	✓	✓.	1	
	Indicating Display	/	✓	✓	✓	✓	✓	✓	1
Service	Programmable Service Reminder	2	✓	✓	✓	✓	✓	1	✓-
	1 Year Limited Warranty	1	/	1	✓	✓	/	/	/
	Material	Stainless 304	Stainless 304	Stainless 304	Stainless 304	Stainless 304	Stainless 304	Stainless 304	Stainless 304
	Lid Type	Transparent with Dome	Transparent with Dome	Transparent with Dome	Transparent with Dome	Transparent with Dome	Transparent with Dome	Transparent with Dome	Transparent
Housing & Dimensions	Width x Length	10.75" x 17.25"	15.00" x 22.50"	15.00" x 22.50"	15.50" x 20.00"	15.50" x 25.00"	21.25" x 24.50"	21.25" x 24.50"	19.00" x 23.50"
	Height (Lid open/closed)	19.00" / 11.00"	24.50" / 12.00"	24.50" / 12.00"	27.00" / 14.00"	23.00" / 13.00"	31.25" / 18.50"	31.25" / 18.50"	-
	Recessed Lifting Cups	*		*		-	1	✓	(4)
	Leveling Legs	2	✓	/	1	1	1	1	1
	Shipping Wt. (pallet not included)	48lbs DB	94,2lbs DB	95lbs	92.2lbs DB	108,7lbs	197.9lbs	206,5lbs	170 lbs / 225 lbs
Optional Seal Bars	Wide Flat Seal (6mm + 1mm Cut-Off Seal)		/	/	/	/	1	1	
	Dual Flat Seal (2 x 4 mm)	1	y	/	1	1	/	1	1
	Dual Convex Seal (2 x 3.5 mm)	,	7	/	7	1	1	1	/
	Top & Bottom Seal		170			-	,	/	/
Optional Features	Inert Gas Flush Kit	-		1	1		J	1	J
	Evacuation Filter Kit	<u> </u>		<u>.</u>	,	,	,	,	,
	Tray for Liquids	/	/	1	7	ý	1	1	Forming Box
	NSF 4" Legs	<u> </u>	Y	· ·					Torring Dox
	230V Single Phase @ 50/60Hz	- /	,	J	1	- J	<i>J</i>	1	1
ساد .	ZOUY OHIGH FILASE W DU/DUNZ		¥*-	~	¥	¥	•	V	

*Depends on type of product, film and operator ability.

DB = double-boxed



中立包装文具有限公司

CHUNG LUP PACKING & STATIONERY CO., LTD.

鍾山集團成員 A Member of the Zhong Shan Group